

PUBLIC ADDRESS, WALL CONTROLLERS



AmiCTL2w

Part no. H11879 EAN 3662009029528

Maximum flexibility on screen.

- › Wall-mounted controller for Ami Series matrices
- 1.31-inch OLED display and rotary encoder
- › Up to 32 programmable menus
- › PoE — White



PRODUCT PAGE ONLINE

audiophony-pa.com/ami/amictl2.html

Manuals, compatible accessories and updates — scan the code or click the address.

[User manual \(PDF\)](#)

Technical specifications

	Clickable rotary encoder + 1.31-inch OLED display
	Up to 32 programmable menus, unlimited functions
	Each function can be renamed; adjustable minimum and maximum limits; configurable rotation increments
	Dual Passwords — Separate Usage and Settings
	Unlimited number of controllers per matrix
	Compatible with the entire Ami line
Power	PoE, 48 V max. — PoE switch required
Power consumption	< 5 W
Maximum cable length	100 m
Connection port	1 × RJ45
Dimensions	86 × 86 × 35 mm
Weight	185 g

Overview

Maximum flexibility on screen.

The AmiCTL2 is the wall-mounted controller in the Ami line for installations that require maximum flexibility. Its clickable rotary encoder and 1.31" OLED display allow you to navigate through up to 32 menus that are fully programmable via AmiControl. Each function can be renamed, its minimum and maximum limits can be set independently, and the rotation increments are configurable.

Security, installation, and compatibility.

A dual-password system protects access to sensitive settings—one for everyday use, the other for advanced settings. Powered via PoE using a single network cable (PoE switch required). Compatible with all matrices in the Ami line; supports an unlimited number of controllers.

Compatible accessories



Ami04
H11872



Ami04D
H11873



Ami08
H11874



Ami08D
H11875



Ami16
H11876



Ami16D
H11877



PoE10-250
H11913

Photo

