

LOW IMPEDANCE AMPLIFIERS

AMP200.4



Part no. B08131 EAN 5420025681315

› Professional 4 channel power amplifier 4 x 200

W rms / 4 ohms



PRODUCT PAGE ONLINE

jb-systems.eu/amp200-4

Manuals, compatible accessories and updates — scan the code or click the address.

[User manual \(PDF\)](#)

Technical specifications

The unit houses 2 separate Class D amplifiers that can be independently configured to provide the following combinations:

Both amps in stereo mode	4 x 200 W rms @ 4 Ω (4 x 100 W rms @ 8 Ω)
Both amps in mono mode	4 x 200 W rms @ 4 Ω (4 x 100 W rms @ 8 Ω)
Both amps in Bridge mode	2 x 400 W rms @ 8 Ω
3 channel mode (2 satellites + sub)	2 x 200 W rms @ 4 Ω (or 2 x 100 W rms @ 8 Ω) + 1 x 400 W rms @ 8 Ω
	120 Hz high-pass filter on/off switch for satellite speakers
	120 Hz low-pass filter on/off switch for the subwoofer

Overview

Professional 4-channel power amplifier in an extremely compact 19" 1U case (H: 44 mm)

Protection against DC faults, high temperatures, overloads and short circuits.

A plastic cover (included) can be installed to prevent access to the level buttons.

Balanced XLR inputs.

speakON® compatible outputs.

Compatible accessories



WEBAMP PRE

B08216

Photo



Photo



Photo



Photo



Photo



Photo

