



## AMP240

Référence: H9904



240 W Public Address amplifier with 4  $\Omega$ /70/100 V output - Works in 4 Ohms / 70 V / 100 V - Safety 24 V - Adjustable input level - 19" rackable - High Pass Filter

- RMS power : 240 W

Output levels / Impedance :

- 100V (42 Ohms)
- 70V (21 Ohms)
- 4 Ohms (31V)
  
- Balanced XLR input
- Balanced XLR output
- Power output on terminals
- 24V DC input on terminal blocks
- Input sensitivity : 01.0V (adjustable)
- Input impedance : 10 KOhms (balanced)
- Frequency response: 70Hz - 18Khz (+/-3 dB)
- T.H.D (1KHz, nominal power): <1%.
- Signal to noise ratio: 90 dB
- Ground Lift Switch
- 400 Hz high-pass filter activated by switch

Power supply:

- AC 100 - 240V, 50/60Hz
- DC24V (safety power supply)
- Power consumption: 361 W

Protections:

- Short circuits
- Thermal
- Overloading
  
- Dimensions (W x H x D): 482 x 88 x 330 mm
- Weight: 13.8 kg
- 19 inch rackable
- Height: 2 units

## Caractéristiques

<b>Brand</b>	Audiophony PA
<b>Power</b>	240 W rms
<b>Impedance</b>	4 Ω

## Galerie photos



---

 **hitmusic**  
Fabrique sensorielle

[www.hitmusic.eu/en/](http://www.hitmusic.eu/en/)