



## AMP240

240 W Public Address amplifier with 4 Ω/70/100 V output

- Works in 4 Ohms / 70 V / 100 V
- Safety 24 V
- Adjustable input level
- 19" rackable
- High Pass Filter



**SKU:** H9904

**Categories:** [100 V amplifiers](#)

**EAN13 :** 3662009009971

**brand** Audiophony PA

- RMS power : 240 W

Output levels / Impedance :

- 100V (42 Ohms)

- 70V (21 Ohms)

- 4 Ohms (31V)

- Balanced XLR input

- Balanced XLR output

- Power output on terminals

- 24V DC input on terminal blocks

- Input sensitivity : 01.0V (adjustable)

- Input impedance : 10 KOhms (balanced)

- Frequency response: 70Hz - 18Khz (+/-3 dB)

- T.H.D (1KHz, nominal power): <1%.

- Signal to noise ratio: 90 dB

- Ground Lift Switch

- 400 Hz high-pass filter activated by switch

Power supply:

- AC 100 - 240V, 50/60Hz
- DC24V (safety power supply)
- Power consumption: 361 W

Protections:

- Short circuits
- Thermal
- Overloading

- Dimensions (W x H x D): 482 x 88 x 330 mm
- Weight: 13.8 kg
- 19 inch rackable
- Height: 2 units

## INFORMATIONS COMPLÉMENTAIRES

<b>Brand</b>	Audiophony PA
<b>Power</b>	240 W rms
<b>Impedance</b>	4 Ω

## GALERIE D'IMAGES



