



AMP240

240 W Public Address amplifier with 4 Ω /70/100 V output - Works in 4 Ohms / 70 V / 100 V - Safety 24 V - Adjustable input level - 19" rackable - High Pass Filter

Référence: H9904



- RMS power : 240 W

Output levels / Impedance :

- 100V (42 Ohms)

- 70V (21 Ohms)

- 4 Ohms (31V)

- Balanced XLR input

- Balanced XLR output

- Power output on terminals

- 24V DC input on terminal blocks

- Input sensitivity : 01.0V (adjustable)

- Input impedance : 10 KOhms (balanced)

- Frequency response: 70Hz - 18Khz (+/-3 dB)

- T.H.D (1KHz, nominal power): <1%.

- Signal to noise ratio: 90 dB

- Ground Lift Switch

- 400 Hz high-pass filter activated by switch

Power supply:

- AC 100 - 240V, 50/60Hz

- DC24V (safety power supply)

- Power consumption: 361 W

Protections:

- Short circuits

- Thermal

- Overloading

- Dimensions (W x H x D): 482 x 88 x 330 mm

- Weight: 13.8 kg

- 19 inch rackable

- Height: 2 units

Caractéristiques

Brand	Audiophony PA
Power	240 W rms
Impedance	4 Ω

Galerie photos

