



AMP600

The AMP600 is a robust, high-impedance Class D amplifier ideal for fixed installations. Output power 600 W. Compatible with 100 V lines only.

Référence: H11708

929,00 € inc. VAT



The AMP600 is a robust, high-impedance Class D amplifier, ideal for fixed installations.

- Output power: 600 W
- Compatible with 100 V lines only
- Class D for optimum energy efficiency
- Continuous temperature management and thermo-regulated fan cooling
- Rear volume control
- Auto-standby after 15 minutes without signal
- Input and output connections via Euroblock connectors for fast, secure installation

Technical specifications:

- Power at 100 V: 600 W
- Output impedance at 100 V: 17 Ohms
- Input sensitivity: 0 dBV/20K Ohms balanced
- Frequency response: 20 Hz - 20 kHz
- THD+N: < 0.1% - S/N: > 100 dB
- Damping factor: > 500 @ 1 kHz
- Power circuit: Class D
- Power supply: PFC switching power supply AC 90-264 V, 50/60 Hz
- Protections: short-circuit, open-circuit, thermal, limiter, ultrasonic and radio frequency
- Connections: input Euroblock GND + - & output Euroblock + -
- Settings: ON/OFF switch on front panel, volume and HPF on rear panel
- Indicators: Signal, -20 dB, Clip, Protect on front panel
- Cooling: thermo-regulated ventilation
- Dimensions: 483 x 88 x 425 mm (2U, 19-inch)
- Weight: 5.8 kg

Caractéristiques

Brand	Audiophony PA
Power	600 W

Galerie photos

