

ACTIVE SUBWOOFERS



BLAST-SUB115A

Part no. B08647 EAN 5420025686471

Power built for large setups.

- › The BLAST-SUB115A is a 15-inch active subwoofer with 600 W RMS of Class D amplification
- › Featuring a built-in DSP designed to integrate seamlessly into any sound system
- › With optimal compatibility with the BLAST line of active speakers



PRODUCT PAGE ONLINE

jb-systems.eu/blast-sub115a

Manuals, compatible accessories and updates — scan the code or click the address.

Technical specifications

Amplification	600 W RMS Class D
Frequency response	35 Hz - 115 Hz
Power supply	AC 230 V / 50 Hz
Max SPL (@1m)	127 dB
Woofer	Sensitivity 96 dB (1W/1m), 15 inches
Audio inputs	XLR 3-pin combo / 6.35 mm jack
Audio outputs	XLR 3-pin (Link)
Controls	Bass boost, DSP, Independent volume, Reverse polarity
Housing	Plywood box, Polyurethane paint finish, Stacking slots
Model size	15"
Function	DSP
Dimensions	600 x 460 x 565 mm
Net weight	37 kg
Sensitivity (1W/1m)	96 dB (1 W / 1 m)
Power	600 W RMS
Family	BLAST

Overview

Power built for large setups.

With its 15-inch woofer and 600 W RMS Class D amplifier, the BLAST-SUB115A delivers the bass reinforcement needed for installations and performances that require higher sound pressure levels. Its built-in DSP ensures precise and controlled reproduction across the entire frequency range, without complex settings or tedious manual adjustments. Its stacking notches make it easy to integrate into larger setups, allowing you to cover large areas with ease.

Power and precision in the bass.

The BLAST-SUB115A covers a frequency range from 35 Hz to 115 Hz, with a maximum SPL of 127 dB and a sensitivity of 96 dB. It delivers powerful and precise bass, capable of supporting audio systems in large spaces without ever losing control.

A design built to last.

Made of plywood and finished with a durable polyurethane paint, the BLAST-SUB115A is designed to withstand the rigors of regular professional use, while maintaining a high-quality finish suitable for both permanent installations and frequent transport.

Connectivity and Installation Ergonomics.

The BLAST-SUB115A features a 3-pin XLR/6.35 mm jack combo input and a Link output for connecting an additional speaker, simplifying on-site wiring. An independent volume control and a polarity switch allow for precise system tuning, while the bass boost function adds extra low-frequency gain when the room or setup requires it.

Technical Specifications:

Speaker:

1 x 15-inch

Power:

600 W RMS — Class D amplification

Frequency response:

35 Hz - 115 Hz

Max SPL:

127 dB

Sensitivity:

96 dB (1 W / 1 m)

DSP:

built-in (BLAST series-compatible preset)

Inputs:

3-pin XLR / 6.35 mm combo jack, IEC

Output:

XLR 3-pin (Link)

Settings:

independent volume control, polarity switch, bass boost

Power supply:

AC 230 V / 50 Hz

Construction:

plywood box, polyurethane paint, stacking notches

Color:

black

IP:

indoor use

Dimensions (W x D x H):

600 x 460 x 565 mm

Weight:

37 kg

Net weight: 37 kg

Compatible accessories



BLAST-10A

B08638



BLAST-12A

B08639



VP-130

B00655



TUB-LINK

H9105

Photo



Photo

