



## **BT-THEATRE 250EZ Mk2**

High power 250W LED theater spotlight with  $14^\circ$  to  $54^\circ$  electronic zoom and excellent low noise cooling

Référence: B06038



- Extremely powerful LED theater spotlight with electronic zoom: Beam angle from 14° to 54°.
- The 250W 3200K warm white LED produces incredible light output that easily outperforms traditional 2kW halogen theater lights!
- Excellent photometric characteristics: CRI / Ra >97, TLCI >98, CQS >94, Rf >93, Rg >100 !
- Filter holder for the use of color filters and eight-leaf barn door included
- No need for heavy and expensive drive blocks!
- Reworked cooling system for extremely quiet operation, low LED temperature and stable light output
- LCD screen for easy navigation through the redesigned configuration menu!
- DMX controlled: 7 different channel modes (8-bit and 16-bit dimming) for maximum flexibility.
- Prepared for wireless DMX: just connect a DONGLE WTR-DMX! (Briteq® code: 4645)
- Flicker-free TV recordings without dimmer noise, thanks to HF PWM dimming: up to 20kHz!
- Manual dimming and focus adjustment: easy alignment of the projector on stage + use on exhibition stands.
- The lamp can be continuously adjusted to imitate the behavior of halogen LED lamp.
- Four intensity variation curves: linear, square, inverted square, S-curve
- In case of DMX failure, the "all off" or "hold" modes will remain available.
- RDM functionality for easy remote configuration: DMX addressing, channel mode, ...
- Lock function to prevent unwanted configuration changes.
- Factory default settings and personal settings can be stored/loaded.
- 3 and 5 pin DMX I/O + Neutrik PowerCON power I/O for easy chaining.

## Caractéristiques

Brand	Briteq
Controllable colours	Warm white
Protection class	IP20
Protocole	DMX, RDM, Wireless DMX



## Références compatibles



PROJECTOR CASE
4
749,00 € inc.

**VAT**Réf: B03285



FIRMWARE UPDATER 2+

109,00 € inc. VAT

Réf: B05019



BT-THEATRE SOFT2

39,00 € inc. VAT

Réf: B06049



BT-THEATRE YOKE

159,00 € inc. VAT

Réf: B06021



## **Galerie photos**







LUX (full on) 117'440	29'360		13'050			7'340			4'700			3'260	
BT-THEATRE250EZ Mk2	_	-										$\neg$	
BEAM: 14°		G H	-	ES	E A	R C	Н						
DISTANCE (m) 1 BEAM Ø (m) 0.25	2 0.49		0.	3 74		0.	4 98		1	5 .23		6 1.47	





