

HIT MUSIC - Fabricant et distributeur en son & lumières

www.hitmusic.eu/en/



BT-VENUELITE4

Référence: B05180

669,00 € inc. VAT



Elegant fanless 4-cell 3000 K white "HI-CRI" spotlight with "escape lighting function

- This elegant white 4-cell spotlight has some very interesting features, making it particularly suitable for lighting auditoriums, concert halls, art galleries, museums and much more.
- It features an **evacuation lighting function**: in the event of a power failure, the spotlight continues to operate for at least 2 hours thanks to the optional internal battery (with built-in charger).
- It's also the ideal tool for rental companies: solid, battery-powered lighting when dismantling equipment after a show, or automatic lighting in the event of a power failure.
- The sturdy die-cast aluminum chassis ensures natural convection cooling: no fan, so totally silent.
- 4 cells, each with COB 3000K and high CRI >90
- Thanks to its high efficiency, it combines high light output with low power consumption!
- Standard 45° reflectors can be easily replaced by optional reflectors with different beam angles: 24°, 60°.
- Cells can be controlled in different configurations: 4 sets, 4 separate or 2 x 2 cells
- Wired DMX/RDM or wireless DMX dongle for easy remote control.
- Can also be operated independently (on/off switch).
- Standard powerCON TRUE1 / XLR 3-pin connections can be quickly converted to XLR 5-pin or fixed-wire connections.
- Power consumption: 160 W
- Weight: 5.6 kg
- Dimensions: 42.3 x 11.2 x 17.9 cm

Caractéristiques

Brand	Briteq		
Controllable colours	Warm white		
Protection class	IP20		
Lux	620 (45°) at 5 m		
Protocole	DMX, RDM, Wireless DMX		
LED type	СОВ		
Function	Manual zoom		

Accessoires recommandés





219,00 € inc. VAT Réf: B05181



BT-VENUELITE4 REFL.CUPS 60DEG

11,90 € inc. VAT Réf: B05183



BT-VENUELITE4 REFL.CUPS 24DEG

11,90 € inc. VAT Réf: B05182



WTR-DMX DONGLE

59,00 € inc. VAT Réf: B04645


Galerie photos











LUX (full on) 10620	2655	1180	665	425	295
BT-VENUELITE 4			0	PTIONAL	
BEAM: 60°					
DISTANCE (m) 1 BEAM Ø (cm) 115	2 231	3 346	4 462	5 577	6 693
LUX (full on) 15525	3880	1725	970	620	430
BT-VENUELITE 4			S	TANDARD	
DISTANCE (m) 1 BEAM Ø (cm) 83	2 166	3 249	4 331	5 414	6 497
LUX (full on) 41400	10350	4600	2590	1660	1150
BT-VENUELITE 4			0	PTIONAL	
BEAM: 24°					
DISTANCE (m) 1 BEAM Ø (cm) 43	2 85	3 128	4 170	5 213	6 255



www.hitmusic.eu/en/