



## BTI-BLIZZARD PROFILE

7890,00 € inc. VAT

Powerful, silent 600W IP65 LED lighting system with cutting module, CMY, CTO, IRIS etc.



SKU: B05571

Categories: [Beam moving head](#), [Hybrid Lyres](#), [Spot moving head](#), [Wash moving head](#)

Tags: [BTI](#)

EAN13 : 5420025655712

brand Briteq

- BTI-BLIZZARD PROFILE is a powerful IP65 head equipped with a cutting module.
- It is equipped with a 600 W LED light source.
- IP65 protection and silent operation: perfect for both indoor and outdoor use!
- A real all-rounder: BEAM, SPOT, WASH and FRAMING!
- Very high light output: 60,610 lux @5m (7°) - 1713 lux @5m (50°).
- Perfect for: concerts, events, theme parks, open-air theaters, etc.
- Wide-range 16-bit electronic zoom, from 7° to 50°, with 16-bit motorized (auto)focus.
- 16-bit adjustable iris: 5 → 100
- Complete framing module with 4 individually controlled blades and +/-60° rotation.
- CMY color system, with several color macros.
- Graduated CTO: 2700K → 6800K
- 6+1 fixed colors, including UV.
- 7 +1 replaceable rotating gobos with fine indexing.
- 10+1 static glass gobos for gobo superposition.
- Non-stop rotating animation wheel with indexing.
- Bi-rotating 4-facet prism.
- 2 gradual frost filters: 1 light + 1 medium.
- Precise strobe with integrated random, pulsed and burst effects.
- Smooth 16-bit dimmer with fast and slow dimming modes.
- Four gradation curves: linear, square, inverted square, S-curve.

- Fast 16-bit pan/tilt movements with position correction and pan/tilt speed channel.
- Super-quiet fan mode for theater applications.
- Uses 35, 41 or 44 DMX channels + RDM function for easy remote configuration.
- Full support for Art-Net™ and sACN!
- Internal web server for additional remote configuration.
- The LCD matrix display ensures easy navigation through the various configuration menus.
- 5-pin DMX I/O + RJ45 I/O + powerCON TRUE1 compatible.
- DMX inputs/outputs compatible with BT-XLR5TO3 kit.
- Equipped with omega brackets for quick installation.
- Dimensions: 42 x 36 x 73 cm
- Weight: 34 kg

## INFORMATIONS COMPLÉMENTAIRES

<b>Brand</b>	Briteq
<b>Protection class</b>	IP65
<b>Function</b>	10 static gobos, 6 colors, 7 rotating gobos, CTO (2700 k to 6800 k), Iris, Linear frost effect, Motorized focus, Motorized frost effect, Motorized zoom, Prime bi-rotary 4 facets
<b>Protocole</b>	Art-Net, DMX, RDM, sACN, Wireless DMX
<b>Lux</b>	1713 lux (50°) at 5 m, 60610 lux (7°) at 5 m
<b>Power</b>	600 W
<b>Type de lampe</b>	LED
<b>Family</b>	BTI

# GALERIE D'IMAGES



LUX (full on)	60610	15150	6735	3790	2425	1685
BTI-BLIZZARD PROFILE						
BEAM: 7°	[Beam profile diagram showing a narrow beam]					
DISTANCE (m)	5	10	15	20	25	30
BEAM Ø (cm)	61	122	183	245	306	367

LUX (full on)	1720	430	191	108	69	48
BTI-BLIZZARD PROFILE						
BEAM: 50°	[Beam profile diagram showing a wide beam]					
DISTANCE (m)	5	10	15	20	25	30
BEAM Ø (cm)	466	933	1399	1865	2331	2797



