



BTX-SATURN

270W LED light head with $8-45^{\circ}$ zoom, CMY, CTO, CTB, UV, Iris color mixing, frost filter, morphing effect, etc.

Référence: B04428

3390,00 € inc. VAT



- High performance headlamp based on a very powerful 270W LED!
- Long range electronic zoom, from 8° to 45° + motorized focus.
- Silent mode for theater applications.
- Fast pan/tilt movements 540° and 270°.
- 16-bit pan/tilt resolution with position correction and pan/tilt speed channel
- CMY color mixing to create many pastel and saturated colors.
- 9 additional fixed colors, including 2 CTO, one CTB and one UV.
- 7 replaceable rotating gobos with fine indexing.
- 9 static gobos for morphing effect.
- Rotating prism with 3 facets.
- Iris module for dynamic effect.
- Variable frost filter for a variable wash effect.
- Aperture diaphragm for excellent logo projection.
- Pulse open/close, ramp and random effects on zoom, iris and frost channels.
- Four dimming curves: linear, square, inverse square, S-curve, slow and fast dimming mode.
- Precise strobe with built-in random effects, pulse and burst.
- Three distance-compensating focuses ensure that the focus is always set to the zoom aperture.
- Uses 25, 27 DMX channels + RDM functionality for easy remote configuration.
- Simple USB firmware update to keep the lyre up to date at all times.
- The matrix LCD screen ensures easy navigation through the various configuration menus.
- 3 and 5 pin DMX inputs/outputs + Neutrik PowerCON TRUE1 inputs/outputs for single series connection.
- Equipped with Omega brackets for quick installation.

Caractéristiques

Brand	Briteq
Protection class	IP20
Controllable colours	Blue, CMY, Green, Red, UV
Function	3-facet rotating circular prism, 7 rotating gobos, 9 colors, 9 static gobos, Frost, Iris, Motorized focus, Motorized zoom
Protocole	DMX, RDM
Lux	31 680 lux (8°) at 5 m
Power	270 W
Type de lampe	LED



Accessoires recommandés

Enga .		
MOVING HEAD CASE 5		
719,00 € inc. VAT		
Réf: B03291		

Galerie photos



LUX (full on) 198'000	31'680	14'080	7'920	3'520	1'980
BTX-SATURN					
BEAM: 8°	LIGH	TRESEA	RCH		
DISTANCE (m) 2 BEAM Ø (m) 0,28	5 0,70	7,5 1,05	10 1,40	15 2,10	20 2,80
LUX (full on) 9'800	1'568	697	392	175	98
BTX-SATURN					
BEAM: 45°	L G I	TRESEA	R C.F		
DISTANCE (m) 2 BEAM \varnothing (m) 1,66	5 4,14	7,5 6,21	10 8,28	15 12,4	20 16,6







