



BTX-SATURN

3390,00 € inc. VAT

270W LED light head with 8-45° zoom, CMY, CTO, CTB, UV, Iris color mixing, frost filter, morphing effect, etc.



SKU: B04428

Categories: [Spot moving head](#)

EAN13 : 5420025644280

brand Briteq

- High performance headlamp based on a very powerful 270W LED!
- Long range electronic zoom, from 8° to 45° + motorized focus.
- Silent mode for theater applications.
- Fast pan/tilt movements 540° and 270°.
- 16-bit pan/tilt resolution with position correction and pan/tilt speed channel
- CMY color mixing to create many pastel and saturated colors.
- 9 additional fixed colors, including 2 CTO, one CTB and one UV.
- 7 replaceable rotating gobos with fine indexing.
- 9 static gobos for morphing effect.
- Rotating prism with 3 facets.
- Iris module for dynamic effect.
- Variable frost filter for a variable wash effect.
- Aperture diaphragm for excellent logo projection.
- Pulse open/close, ramp and random effects on zoom, iris and frost channels.
- Four dimming curves: linear, square, inverse square, S-curve, slow and fast dimming mode.
- Precise strobe with built-in random effects, pulse and burst.
- Three distance-compensating focuses ensure that the focus is always set to the zoom aperture.
- Uses 25, 27 DMX channels + RDM functionality for easy remote configuration.
- Simple USB firmware update to keep the lyre up to date at all times.
- The matrix LCD screen ensures easy navigation through the various configuration menus.
- 3 and 5 pin DMX inputs/outputs + Neutrik PowerCON TRUE1 inputs/outputs for single series connection.

- Equipped with Omega brackets for quick installation.

INFORMATIONS COMPLÉMENTAIRES

Brand	Briteq
Protection class	IP20
Controllable colours	Blue, CMY, Green, Red, UV
Function	3-facet rotating circular prism, 7 rotating gobos, 9 colors, 9 static gobos, Frost, Iris, Motorized focus, Motorized zoom
Protocole	DMX, RDM
Lux	31 680 lux (8°) at 5 m
Power	270 W
Type de lampe	LED

GALERIE D'IMAGES



LUX (full on)	198'000	31'680	14'080	7'920	3'520	1'980
BTX-SATURN						
BEAM: 8°						
DISTANCE (m)	2	5	7,5	10	15	20
BEAM Ø (m)	0,28	0,70	1,05	1,40	2,10	2,80
LUX (full on)	9'800	1'568	697	392	175	98
BTX-SATURN						
BEAM: 45°						
DISTANCE (m)	2	5	7,5	10	15	20
BEAM Ø (m)	1,66	4,14	6,21	8,28	12,4	16,6



