



DZ-CTL2OUT

DZ-MATRIX input and output volume control box. It has two balanced analog outputs. LCD screen to view levels and routing

Référence: H11397

259,00 € inc. VAT



Pump up the volume.

The box allows you to select a source and adjust its volume on a previously chosen output. As for its display, it allows you to choose the channel you want to select and then to adjust its volume.

The control box is connected to digital channels 9/10, 11/12 of the matrix*.

DZ-CTL2OUT has 2 balanced analog outputs on the back to connect an amplified system for example.

The DZ-MATRIX Setting Software allows you to:

- The name of the box can be changed with the DZ-MATRIX setting software
- The software allows to give access to the sources and outputs in order to limit the settings for the end user
- Password lock and adjustable screen saver

**Use CAT5e or CAT6 cable with a maximum length of 100 m.*

Characteristic :

2 analog outputs

Symmetrical

- Connectors: 2 x 3-pin terminal blocks, 5 mm pitch
- Impedance: 240 Ohms
- Maximum output power : + 20 dBu
- Frequency response at 0 dB : 20 Hz ~ 20 kHz +/- 1.5 dB
- Dynamic range: -107 dB max, A-weighted
- Crossover distortion : -87 dB max. Weighting A

LCD display

- Volume control: $-\infty \sim +15$ dB

Ports

- Network RD to DZ-MATRIX, RJ45, 100 m maximum of CAT 5E cable (or higher)


Dimensions

- W x H x D: 147 x 86 x 47 mm

Caractéristiques

Brand	Audiophony PA
Finish colour	White

Références compatibles

 <p>DZ-MATRIX 1299,00 € inc. VAT Réf: H11393</p>				
--	--	--	--	--

Galerie photos

