



EXTLine134W

IP56 4 x 4" + 1" floor-standing column - 130 W RMS - 100 V/ 8 ohms - Robust, weather-resistant, all-aluminum column - High-quality components for a highly musical sound - Operates on 100 V or 8 ohms

Référence: H11616

529,00 € inc. VAT



- Operates at 100 V or 8 ohms
- Power: 130 W RMS at 8 ohms 30/60/120 W at 100 V
- Components: 4 x 4" Kevlar waterproof drivers and 1 x 1" compression driver
- Dispersion (-6 dB): 100° x 50° (H x V)
- Sensitivity (1 W/1 m): 94 dB
- Frequency response: 120 - 18,000 Hz
- SPL: 115 dB continuous, 121 dB max.
- Connectors: connectors with cable glands
- Aluminum body with aluminum grille and acoustic foam
- ABS body with aluminum grille and acoustic foam
- Silicone plugs and stainless steel screws
- Foam and textile protection against dust and splashes
- Degree of protection: IP56 (protection against dust and rain)
- Dimensions: 704 x 127 x 144 mm
- Net weight: 9 kg

SPL (significant values)

- 1 m : 121 dB
- 5 m : 107 dB
- 7 m : 104 dB
- 10 m : 101 dB
- 15 m : 97 dB
- 20 m : 95 dB
- 30 m : 91 dB

Caractéristiques

Brand	Audiophony PA
Finish colour	White
Impedance	8 Ω
Voltage	100 V
Model size	4"
Power	30 W, 60 W, 120 W, 130 W
Protection class	IP56
SPL max (@1m)	121 dB
Family	EXT

Références compatibles



SUPlineW

35,00 € inc.

VAT

Réf: H11618



FIXlineW

28,00 € inc.

VAT


Réf: H11620

Galerie photos





pa audiophony
public-address



EXTLine 134W

Power : 130 W RMS

Input voltage : 100V/8Ω

Speaker wiring

1+ / 2-

