



BEAMER FC COURSE - OUTDOOR

High Power RGBB LED floodlight with 14 OSRAM 5W LEDs for outdoor use - IP65

Référence: B05511

389,00 € inc. VAT












- Additional "16-BIT TOUR" mode with 16-bit color control (R, G, B and B controlled on 2 channels: coarse + fine)
- Very powerful RGB LED floodlight equipped with 14 x 5W OSRAM four-color LEDs:
 - Unwanted dark tones are completely eliminated
 - Perfect color mix evenly distributed, even at close range
 - Beam angle: 14°.
 - **IP65**
- This LED floodlight is your first choice: it can light up small, medium or large scenes, but will also fit perfectly into architectural lighting.
- Perfect alternative to traditional PAR64 floodlights: only 65W power consumption at full intensity and no need for bulky dimmer blocks!
- The adoption of LED technology allows for significant energy savings compared to halogen lamp equipment!
- Several DMX operating modes: 4, 5, 6, 7, 9, 10, 15 channels
- Thanks to all kinds of special functions, this projector is chosen by professional lighting designers:
 - Color temperature presets from 3200 K to 10,000 K
 - RRGB calibration
 - Different gradation curves
 - Addressing by ID
 - Neutrik PowerCon input/output (max. 24 units)
 - 3-pin + 5-pin DMX input/output
 - Recall of custom programs via DMX
 - Menu-driven LED display on the back with password protection
 - Tempered glass lens protection
- The 1200 Hz LED is also suitable for TV studios (no interference with TV cameras)
- Completely silent: the projector is cooled by natural air circulation, so there is no need for noisy fans!
- The lightweight aluminum housing has two suspension brackets so that it is also possible to use this projector on the ground.
- **NOTE: This product has an IP65 rating for outdoor installation under normal conditions (not exposed to sea water).**

Caractéristiques

Brand	Briteq
Controllable colours	RGBW
Protection class	IP65
Protocole	DMX

Références compatibles

 <p>SIGNAL LINK CABLE 5M</p> <p>14,90 € inc. VAT</p> <p>Réf: B04903</p>	 <p>SIGNAL LINK CABLE 10M</p> <p>27,00 € inc. VAT</p> <p>Réf: B04904</p>	 <p>SIGNAL LINK CABLE 1,5M</p> <p>7,00 € inc. VAT</p> <p>Réf: B04908</p>	 <p>POWERLINK CABLE 5m</p> <p>35,00 € inc. VAT</p> <p>Réf: B04324</p>	 <p>POWERLINK CABLE 10m</p> <p>59,00 € inc. VAT</p> <p>Réf: B04913</p>
 <p>POWERLINK CABLE 1,5m</p> <p>17,90 € inc. VAT</p> <p>Réf: B04911</p>	 <p>LDP-Powercable 5M</p> <p>19,90 € inc. VAT</p> <p>Réf: B05158</p>	 <p>LDP-Powercable 2M</p> <p>10,90 € inc. VAT</p> <p>Réf: B05157</p>	 <p>PROJECTOR CASE 3</p> <p>590,00 € inc. VAT</p> <p>Réf: B03280</p>	

Galerie photos



