

LIVE MIXERS


EQUIPMENTS

MPX12

Part no. H10907 EAN 3662009019635

Mono channels.

- › 12 channel mixer with compressor
- › Effects and USB / SD / Bluetooth player



PRODUCT PAGE ONLINE

audiophony.com/en/product/MPX12

Manuals, compatible accessories and updates — scan the code or click the address.

Technical specifications

Mic inputs	Balanced
Frequency response	10Hz - 30KHz, +/-3dB
THD (THD&N)	0.03% @ +4dBu, 22Hz-20KHz A-weighted
Compression	Gain: 0-9dB, Threshold: 20dB 5dB
Signal-to-noise ratio	115 dB
Line inputs	Balanced
Frequency response	10Hz - 30KHz, +/-3dB
THD (THD&N)	0.005% @ +4dBu, 22Hz-20KHz A-weighted
Maximum gain	75 dBu Microphone input Master output

Overview

Mono channels.

Stereo channels.

Line inputs: Balanced / Unbalanced

Frequency response: 10Hz - 55KHz, +/-3dB

THD (THD&N): 0.005% @ +4dBu, 22Hz-20KHz A-weighted

Impedances.

Mic inputs: 1.4 K Ohms

Line inputs: 10 K Ohms

Other inputs: 10 K Ohms or more

Recording output: 1 K Ohms

Other outputs: 120 Ohms

Mono channel equalization.

High: +/-15dB @ 12 KHz

Mid : +/-15dB @ 2,5 KHz

Low : +/-15dB @ 45 Hz

Stereo channel equalization.

High : +/-15dB @ 12 KHz

Low : +/-15dB @ 60 KHz

Multi-effect : 24-bit analog-to-digital converter, 16 programs

Power supply: AC100~240V 50/60 Hz

Dimensions: (L x W x E): 330 x 392 x 92 mm


Weight: 5.2 kg

Compatible accessories



MPX12-RACK

H10986



MIC-DESKevo

H11768

Photo



Photo

