



PILOTctl4x4 B

2.4 GHz wall-mounted DMX controller with 4 RGB and RGBW zones

Référence: H11702

49,00 € inc. VAT



PILOTctl4x4 wall controllers are touch-sensitive control interfaces. The control signal is transmitted wirelessly in 2.4GHz mode to the driver. A wired DMX output can also be used to connect drivers or other DMX products. The rear connection block is compatible with standard Legrand back boxes.

Combined with the TAPEDRIVER-RF4 BLE, they allow you to control your LED ribbon installations, offering dimming, color adjustment and 4-zone management functions. These controllers are available in white or black finish.

PILOTctl4x4: control of RGB and RGBW LED ribbons.

- **Electrical data**

- Input voltage: AC 90 ~ 265 V
- RF frequency: 2.4 GHz
- RF distance: < 20 m
- Wired control: DMX 512
- Power consumption: < 0.58 W / < 1.1 W
- Application range: RGB/RGBW

- **Special features**

- Available PWM frequencies: 2 KHz / 15 KHz
- Output dimming: 1024 levels
- Speeds: 1024 levels
- RF connection distance: up to 20 m

- **Operating environment**

- Ambient temperature: 0°C to + 45°C
- Protection class: IP20

- **Physical characteristics**

- Dimensions: 86 x 86 x 32
- Weight: 120 g
- Color: black

Caractéristiques

Brand	Contest Dynamic Lighting
Controllable colours	RGB, RGBW
Function	2.4 GHz, DMX
Protection class	IP20
Finish colour	Black

Références compatibles



**TAPEDRIVER-RF4
BLE**

**34,00 € inc.
VAT**

Réf: H11707

Galerie photos

