



PILOTctl-4x2 W

2.4 GHz and DMX wall controller - 4 zones - White/CCT

Référence: H11701

49,00 € inc. VAT



The PILOTctl-4×2 wall-mounted controller is a touch-sensitive control interface specially designed for monochrome or CCT LED ribbon installations. The control signal is transmitted wirelessly in 2.4GHz mode to the driver, and a wired DMX output is also available for connecting drivers or other DMX products. The rear connection block is compatible with the standard format of Legrand back boxes. In conjunction with the TAPEDRIVER-RF4 BLE, the PILOTctl-4x2 allows easy dimming and control of four zones.

This model is available in white or black finish, offering elegant integration in a variety of environments.

• Electrical data

 \circ Input voltage: AC 90 \sim 265 V

RF frequency: 2.4 GHz
RF distance: < 20 m
Wired control: DMX 512

 \circ Power consumption: < 0.58 W / < 1.1 W \circ Application range: Monochrome / CCT

Special features

o Output gradations: 1024 levels

o Speeds: 1024 levels

o RF connection distance: up to 20 m

• Operating environment

Ambient temperature: 0°C to + 45°C

Protection class: IP20Physical characteristics

Weight: 120 gColor: white

Caractéristiques

Brand	Contest Dynamic Lighting
Controllable colours	1 colour, CLA
Function	2.4 GHz, DMX
Protection class	IP20
Finish colour	White



Références compatibles

TAPEDRIVER-RF4 BLE		
34,00 € inc. VAT		
Réf: H11707		

Galerie photos

