



SLI1000.2

Référence: H11636

899,00 € inc. VAT



Class D amplifier, 2 x 900 W RMS at 4 ohms and 1000 W at 100 V

The SLI1000.2 is a compact, powerful Class D low-impedance amplifier, delivering 2 x 900 W at 4 ohms. It features volume control and LED indicators for signal, clip and protection, ensuring intuitive, safe operation. Connections are made via combo and speakON plugs, offering great versatility and easy installation. What's more, the SLI1000.2 is equipped with a crossover and 100 V mode, making it ideal for applications requiring high power and high-quality audio performance. - Power (1 active channel): 4 Ω (RMS) 1200 W - Power (stereo mode): 4 Ω (RMS) 900 W x 2, 8 Ω (RMS) 600 W x 2 - Power (bridge mode): 4 Ω (RMS) 2400 W, 8 Ω (RMS) 1800 W - Power (70/100 V mode): 1000 W / 70 V, 1000 W / 100 V - Input sensitivity: 0.9 - 1.1 V (0 +/- 1 dBV) - Input impedance: 10k unbalanced - Frequency response: 20 Hz - 20 kHz (+/- 1 dB) - Voltage gain: 30 dB (+/- 0.5 dB)

- THD+N : < 0.1% - S/N : > 98 dB - Damping factor :

> 200 • Circuit de puissance : Alimentation à découpage classe D • Alimentation : AC 220 - 240 V, 50/60 Hz • Protections : Court-circuits, Circuit ouvert, Thermique, Limiteur, Ultrasons et radio fréquences • Connexions : INPUT 2x Combo LINK 2x XLR & OUTPUT 2x speakON • Réglages : Switch ON/OFF en façade et volume, Sélecteur mode à l'arrière • Voyants : SIGNAL: green LED, CLIP: red LED, PROTECTION: red LED • Dimensions : 483 x 44 x 360 (mm) 1U 19 pouces • Poids : 5,7 kg

Caractéristiques

Brand	Audiophony
Power in 4 Ω	2 x 900 W rms
Power in 8 Ω	2 x 600 W rms
Bridge mode at 4 Ω	1 x 2400 W rms
Bridge mode at 8 Ω	1 x 1800 W rms
Function	Bridge
Family	SLI

Galerie photos



www.hitmusic.eu/en/