



SLI300.2

Référence: H11634

429,00 € inc. VAT



Class D amplifier, 2 x 270 W RMS at 4 ohms

The SLI300.2 is a compact and powerful Class D low-impedance amplifier, delivering 2 x 270 W at 4 ohms. It features a volume control and LED indicators for signal, clip and protection, offering intuitive, safe operation. Connections are made via combo and speakON plugs, ensuring great versatility and easy installation. The SLI300.2 is ideal for applications requiring reliable power and high-quality audio performance.

- Power (1 active channel): 4 Ω (RMS) 300 W - Power (stereo mode): 4 Ω (RMS) 270 W x 2, 8 Ω (RMS) 150 W x 2 - Power (bridge mode): 4 Ω (RMS) 900 W, 8 Ω (RMS) 600 W - Input sensitivity: 0.9-1.1 V (0 +/- 1 dBV) - Input impedance: 20 k balanced - Frequency response: 20 Hz - 20 kHz (+/- 1 dB) - Voltage gain: 30 dB (+/- 0.5 dB)

- THD+N : < 0.05 % - S/N :
> 98 dB

- Damping factor : > 180 • Circuit de puissance : Alimentation à découpage classe D

- Power supply: AC 220-240 V, 50/60 Hz

- Protections: Short-circuit, Open circuit, Thermal, Limiter, Ultrasonic and radio frequency - Connections: INPUT 2 x Combo LINK 2 x XLR & OUTPUT 2 x speakON - Settings: ON/OFF switch on front panel and volume, Mode selector on rear panel - Indicators: SIGNAL: green LED, CLIP: red LED, PROTECTION: red LED

- Dimensions: 483 x 44 x 360 (mm) 1U 19-inch

- Weight : 5 kg

Caractéristiques

Brand	Audiophony
Power in 4 Ω	2 x 270 W rms
Power in 8 Ω	2 x 150 W rms
Bridge mode at 4 Ω	1 x 900 W rms
Bridge mode at 8 Ω	1 x 600 W rms
Function	Bridge
Family	SLI

Galerie photos



www.hitmusic.eu/en/