


SLI300.2

429,00 € inc. VAT

Class D amplifier, 2 x 270 W at 4 ohms



SKU: H11634

Categories: [Low impedance amplifiers](#)

Tags: [New](#)

EAN13 : 3662009027135

brand Audiophony

The SLI300.2 is a compact and powerful Class D low-impedance amplifier, delivering 2 x 270 W at 4 ohms. It features a volume control and LED indicators for signal, clip and protection, offering intuitive, safe operation. Connections are made via combo and Speakon plugs, ensuring great versatility and easy installation. The SLI300.2 is ideal for applications requiring reliable power and high-quality audio performance.

- **Power (1 active channel):** 4 Ω (RMS) 300 W
- **Power (stereo mode) :**
 - 4 Ω (RMS) 270 W x 2
 - 8 Ω (RMS) 150 W x 2
- **Power (bridge mode) :**
 - 4 Ω (RMS) 900 W
 - 8 Ω (RMS) 600 W
- **Power (70/100 V mode) :** NC
- **Input sensitivity:** 0.9-1.1 V (0 +/- 1 dBV)
- **Input impedance:** 20 k balanced
- **Frequency response:** 20 Hz - 20 kHz (+/- 1 dB)
- **Voltage gain:** 30 dB (+/- 0.5 dB)
- **THD+N:** < 0.05
- **S/N:** > 98 dB
- **Damping factor:** > 180
- **Power circuit:** Class D switching power supply
- **Power supply:** AC 220-240 V, 50/60 Hz
- **Protections:**

- Short circuits
- Open circuit
- Thermal
- Limiter
- Ultrasound and radio frequency
- **Connections:** INPUT 2x Combo LINK 2x XLR & OUTPUT 2x Speakon
- **Settings :**
 - Front ON/OFF switch and volume
 - Rear mode selector
- **Indicators :**
 - SIGNAL: green LED
 - CLIP: red LED
 - PROTECTION: red LED
- **Dimensions:** 483 x 44 x 360 (mm) 1U 19-inch
- **Weight:** 5.0 kg

INFORMATIONS COMPLÉMENTAIRES

Brand	Audiophony
Power in 4 Ω	2 x 270 W rms
Power in 8 Ω	2 x 150 W rms
Bridge mode at 4 Ω	1 x 900 W rms
Bridge mode at 8 Ω	1 x 600 W rms
Function	Bridge
Family	SLI

