



## SLI300.2

Class D amplifier, 2 x 270 W RMS at 4 ohms

Référence: H11634

**429,00 € inc. VAT**

The SLI300.2 is a compact and powerful Class D low-impedance amplifier, delivering 2 x 270 W at 4 ohms. It features a volume control and LED indicators for signal, clip and protection, offering intuitive, safe operation. Connections are made via combo and speakON plugs, ensuring great versatility and easy installation. The SLI300.2 is ideal for applications requiring reliable power and high-quality audio performance.

- Power (1 active channel): 4  $\Omega$  (RMS) 300 W - Power (stereo mode): 4  $\Omega$  (RMS) 270 W x 2, 8  $\Omega$  (RMS) 150 W x 2 - Power (bridge mode): 4  $\Omega$  (RMS) 900 W, 8  $\Omega$  (RMS) 600 W - Input sensitivity: 0.9-1.1 V (0 +/- 1 dBV) - Input impedance: 20 k balanced - Frequency response: 20 Hz - 20 kHz (+/- 1 dB) - Voltage gain: 30 dB (+/- 0.5 dB)

- THD+N : < 0.05 % - S/N :

> 98 dB

- Damping factor : > 180 • Circuit de puissance : Alimentation à découpage classe D

- Power supply: AC 220-240 V, 50/60 Hz

- Protections: Short-circuit, Open circuit, Thermal, Limiter, Ultrasonic and radio frequency - Connections: INPUT 2 x Combo LINK 2 x XLR & OUTPUT 2 x speakON - Settings: ON/OFF switch on front panel and volume, Mode selector on rear panel - Indicators: SIGNAL: green LED, CLIP: red LED, PROTECTION: red LED

- Dimensions: 483 x 44 x 360 (mm) 1U 19-inch

- Weight : 5 kg

## Caractéristiques

<b>Brand</b>	Audiophony
<b>Power in 4 <math>\Omega</math></b>	2 x 270 W rms
<b>Power in 8 <math>\Omega</math></b>	2 x 150 W rms
<b>Bridge mode at 4 <math>\Omega</math></b>	1 x 900 W rms
<b>Bridge mode at 8 <math>\Omega</math></b>	1 x 600 W rms
<b>Function</b>	Bridge
<b>Family</b>	SLI

## Galerie photos

