


SLI500.2

519,00 € inc. VAT

Class D amplifier, 2 x 450 W at 4 ohms



SKU: H11635

Categories: [Low impedance amplifiers](#)

Tags: [New](#)

EAN13 : 3662009027142

brand Audiophony

The SLI500.2 is a compact and powerful Class D low-impedance amplifier, delivering 2 x 450 W at 4 ohms. It's equipped with a volume control and LED indicators for signal, clip and protection, guaranteeing intuitive, safe operation. Connections are made via combo and Speakon plugs, offering great versatility and easy installation. The SLI500.2 is ideal for applications requiring reliable power and high-quality audio performance.

- **Power (1 active channel):** 4 Ω (RMS) 600 W
- **Power (stereo mode) :**
 - 4 Ω (RMS) 450 W x 2
 - 8 Ω (RMS) 250 W x 2
- **Power (bridge mode) :**
 - 4 Ω (RMS) 1200 W
 - 8 Ω (RMS) 900 W
- **Power (70/100 V mode) :** NC
- **Input sensitivity:** 0.9 - 1.1 V (0 +/- 1 dBV)
- **Input impedance:** 10 k unbalanced
- **Frequency response:** 20 Hz - 20 kHz (+/- 1 dB)
- **Voltage gain:** 30 dB (+/- 0.5 dB)
- **THD+N:** < 0.05%
- **S/N:** > 98 dB
- **Damping factor:** > 180
- **Power circuit:** Class D switching power supply
- **Power supply:** AC 220 - 240 V, 50/60 Hz

- **Protections:**
 - Short circuits
 - Open circuit
 - Thermal
 - Limiter
 - Ultrasound and radio frequency
- **Connections:** INPUT 2x Combo LINK 2x XLR & OUTPUT 2x Speakon
- **Settings :**
 - Front ON/OFF switch and volume
 - Rear mode selector
- **Indicators :**
 - SIGNAL: green LED
 - CLIP: red LED
 - PROTECTION: red LED
- **Dimensions:** 483 x 44 x 360 (mm) 1U 19-inch
- **Weight:** 5.1 kg

INFORMATIONS COMPLÉMENTAIRES

Brand	Audiophony
Power in 4 Ω	2 x 450 W rms
Power in 8 Ω	2 x 250 W rms
Bridge mode at 4 Ω	1 x 1200 W rms
Bridge mode at 8 Ω	1 x 900 W rms
Function	Bridge
Family	SLI

