



SLI500.2

Class D amplifier, 2 x 480 W RMS at 4 ohms

Référence: H11635

519,00 € inc. VAT

The SLI500.2 is a compact and powerful Class D low-impedance amplifier, delivering 2 x 450 W at 4 ohms. It's equipped with a volume control and LED indicators for signal, clip and protection, guaranteeing intuitive, safe operation. Connections are made via combo and speakON plugs, offering great versatility and easy installation. The SLI500.2 is ideal for applications requiring reliable power and high-quality audio performance.

- Power (1 active channel): 4 Ω (RMS) 600 W - Power (stereo mode): 4 Ω (RMS) 480 W x 2, 8 Ω (RMS) 250 W x 2 - Power (bridge mode): 4 Ω (RMS) 1200 W, 8 Ω (RMS) 900 W - Input sensitivity: 0.9 - 1.1 V (0 +/- 1dBV) - Input impedance: 10k unbalanced - Frequency response: 20 Hz - 20 kHz (+/- 1dB) - Voltage gain: 30 dB (+/- 0.5 dB)

- THD+N : < 0.05% - S/N : > 98 dB

- Damping factor : > 180 • Circuit de puissance : Alimentation à découpage classe D • Alimentation : AC 220 - 240 V, 50/60 Hz • Protections : Court-circuits, Circuit ouvert, Thermique, Limiteur, Ultrasons et radio fréquences • Connexions : INPUT 2 x Combo LINK 2 x XLR & OUTPUT 2 x speakON • Réglages : Switch ON/OFF en façade et volume, Sélecteur mode à l'arrière • Voyants : SIGNAL: green LED, CLIP: red LED, PROTECTION: red LED

- Dimensions: 483 x 44 x 360 (mm) 1U 19-inch

- Weight: 5.1 kg

Caractéristiques

Brand	Audiophony
Power in 4 Ω	2 x 480 W rms
Power in 8 Ω	2 x 250 W rms
Bridge mode at 4 Ω	1 x 1200 W rms
Bridge mode at 8 Ω	1 x 900 W rms
Function	Bridge
Family	SLI

Galerie photos

