



TAPEDIMMER-RF1

Dimmer 1 x 20 A 12 - 24 VDC 2.4 GHz

Référence: H11706

26,00 € inc. VAT



The TAPEDIMMER-RF1 allows manual dimming via a button, as well as dimming via 2.4GHz remote control (REMOTECTL4x2 or PILOTCTL-4x2 models). By default, it can be controlled by any remote control in any zone.

It is also possible to assign the TAPEDIMMER-RF1 to a specific zone on the remote control. In this case, it is necessary to synchronize the RF codes before installation.

- **Operating voltage:** DC 12~24 V
- **Output:** 1 channel
- **Memory:** Yes
- **PWM frequency:** 2 KHz (default), 500 Hz, 1K Hz, 4 KHz, 7.8 KHz and 15.6 KHz
- **Maximum power output:**
 - PWM \leq 2 KHz : 20 A ; 480 W / 24 V
 - PWM = 4/7.8 KHz : 15 A ; 360 W / 24 V
 - PWM = 15.6 KHz : 10 A ; 240 W / 24 V
- **Protection:** Against short circuits
- **Operating temperature:** -20 ~ 60°C
- **Static power consumption:** < 1 W
- **Dimensions:** 103 x 40 x 24 mm
- **Weight:** 65 g

Caractéristiques

Brand	Contest Dynamic Lighting
Controllable colours	1 colour
Function	2.4 GHz, Wireless remote control (not included)
Protection class	IP20

Références compatibles



REMOTEctI-4x4

**22,00 € inc.
VAT**

Réf: H11704



REMOTEctI-4x2

**22,00 € inc.
VAT**

Réf: H11705

Galerie photos

