



TAPEDRIVER-RF4 BLE

Référence: H11707

34,00 € inc. VAT



Driver 4 x 4 A 12-24 VDC 2.4 GHz BLE-MESH

The TAPEDRIVER-RF4 BLE driver allows connection of ribbons from 1 to 4 colors. It requires a 12 or 24 V power supply for a maximum output of 4 x 4 A.

It can be controlled by wall-mounted controllers or remote controls in 2.4 GHz mode.

The drivers can also be wired for greater range and perfect synchronization. **TAPEDRIVER-RF BLE uses BLE-MESH technology to deploy a Bluetooth mesh network of connected objects.**

• **Electrical data**

- Input voltage: 12~24 V DC
- Output voltage: 4 x 12~24 V DC per channel max.
- Output current :
 - PWM 2 KHz: 4 x 8 A
 - PWM 15 KHz: 4 x 4 A
- Output power :
 - PWM 2 KHz: 384 W / 12 V; 768 W / 24 V
 - PWM 15 KHz: 192 W / 12 V; 384 W / 24 V
- Output type: DC voltage

• **Special features**

- Available PWM frequencies: 2 KHz / 15 KHz
- Output dimming: 1024 levels
- Speeds: 1024 levels
- RF connection distance: up to 20 m
- Protection: against short circuits

• **Operating environment**

- Ambient temperature: 0°C to +45°C
- IP rating: 20

• **Physical characteristics**

- Dimensions: 115 x 70 x 24 mm
- Weight: 125 g

Caractéristiques

Brand	Contest Dynamic Lighting
Controllable colours	1 colour, CLA, RGB, RGBW
Function	2.4 GHz, BLE-MESH, Wireless remote control (not included)
Voltage input	12 V, 24 V
Protection class	IP20

Accessoires recommandés



PILOTctl4x4 B

49,00 € inc. VAT
Réf: H11702



REMOTectl-4x4

22,00 € inc. VAT
Réf: H11704



PILOTctl-4x2 B

49,00 € inc. VAT
Réf: H11700



PILOTctl-4x2 W

49,00 € inc. VAT
Réf: H11701



PILOTctl4x4 W

49,00 € inc. VAT
Réf: H11703



REMOTectl-4x2

22,00 € inc. VAT
Réf: H11705

Galerie photos

