



## Ti154

Amplifier 4x 150W under 4 Ohms or 2x 300W under 8 Ohms - 1 unit

**Référence:** H10412

- Class D amplification
- Switching power supply for very low weight
- Stereo, parallel or bridge modes of operation
- Independent limiter for each channel
- Highly accurate and independent level control for each channel
- Indicator LEDs for displaying the status of the amplifier
- Convection cooling
- Balanced inputs on XLR combo plug and TRS jack
- Outputs on screw terminals/banana or Speakon® 4 points
- Independent thermal and DC current protection on each channel
- Compatible with 19" format for 1 unit high rack mounting
- Stereo Power :
  - 4 x 150 Wrms at 4Ω
  - 4 x 80 Wrms at 8Ω
- Mono clamped power :
  - 2 x 300 Wrms under 8Ω
- **Compact and light**
- **Quiet operation**
- **Stereo mode for up to 8 speakers**
- LINK FOR MORE INFORMATION AND DOWNLOADS: [Ti154](#)

## Caractéristiques

<b>Brand</b>	Audiophony
<b>Power in 4 Ω</b>	4 x 150 W rms
<b>Power in 8 Ω</b>	4 x 80 W rms
<b>Bridge mode at 8 Ω</b>	2 x 300 W rms
<b>Function</b>	Bridge
<b>Family</b>	Ti

## Galerie photos

