



Ti500

Référence: H9673

429,00 € inc. VAT



Class D amplifier, 2 x 250 W RMS at 4 ohms or 1 x 500 W RMS at 8 ohms

Because quiet sound is important in certain conditions, Audiophony has created the Ti500. Whether for theater, studio or installation, the Ti500 offers totally silent operation. This Class D amplifier, equipped with a switch-mode power supply, guarantees impeccable sound reproduction in an ultra-compact format. - 4 Ω RMS stereo power (minimum): 2 x 250 W RMS - 8 Ω RMS stereo power: 2 x 130 W RMS - 8 Ω bridged mono power (minimum): 1 x 500 W RMS

- Signal to noise ratio : Less than 90 dB
 - Input sensitivity: 4 dBu +/-2 dB - Distortion at 1 kHz and 1/2 power: Less than 0.1% - Crossover distortion at full power: -65 dB at 1 kHz - Frequency response (4 Ω/1 W): +0.5 dB; 20 Hz-20 kHz - Input impedance: 15 kΩ unbalanced / 30 kΩ balanced - Clip level: 0 dB - Cooling: Convection - Input connectors: XLR plug and TRS jack balanced + RCA unbalanced - Output connectors: Screw terminals + Speakon® 4-pin - Front panel settings: Power switch / Level 1 and 2 settings - Rear panel settings: Operating mode selector - Indicators: Protect (red) / Clip (yellow) / Signal (green) - Protections: Against short-circuit / Against voltage and thermal drift - Power supply: 100/230 VAC - 50/60 Hz - Dimensions: 482 mm x 44 mm x 330 mm - Net weight: 4.7 kg

Caractéristiques

Brand	Audiophony
Power in 4 Ω	2 x 250 W rms
Power in 8 Ω	2 x 130 W rms
Bridge mode at 8 Ω	1 x 500 W rms
Function	Bridge
Family	Ti

Galerie photos



 **hitmusic**
Fabrique sensorielle

www.hitmusic.eu/en/