



VBAR-50DW

Architectural floodlight IP66 12 LEDs 2700-5600 K 50 W 15 × 30° - LEDs 2700-5600 K 50 W 15 × 30°
- LEDs 2700-5600 K 50 W

Référence: H11382

549,00 € inc. VAT



- Power: 50 W
- LEDs: 12 LEDs 4 W Dynamic White (2700-5600 K)
- Lens aperture: 15° x 30° asymmetrical
- Brightness: 2355 lm - 325 lux at 5 m
- Color rendering index (CRI): 95
- Power consumption: 52 W
- Dimensions: 484 x 117 x 53 mm
- Weight: 3.7 kg
- Connections: DMX/Power via hybrid IN and OUT cables with IP67 plugs
- Parameterization: VRDM-Control external box for RDM parameterization
- RDM console compatibility: Yes, for basic parameters (DMX address, DMX mode, version, etc.).
- How to use :
 - Standalone: Master/Slave and Single
 - DMX: 2 to 4 channels
- Macro: Macros can be created for use in Master/Slave or Single mode.
- Power supply: 110-240 V / 50-60 Hz
- Refresh rate: Selectable from 900 Hz to 3600 Hz
- Cooling : Convection
- Finish: Cast aluminium, epoxy-painted grey-white RAL 9002
- Degree of protection: IP66 (resistant to dust and water spray from all directions)
- Shock resistance: IK07 (protected against an impact of 2 joules, equivalent to a 500 g object falling from 40 cm)
- Pressure control: Sealed diaphragm depressurization valve
- Accessories: VC-Start power cord, IP plugs, flow switch

Caractéristiques

Brand	Contest Architectural Lighting
Controllable colours	Cold white, Natural white, Warm white
Power	50 W
Protocole	DMX, RDM
Type de lampe	LED

Références compatibles



VRDM-CONTROL

379,00 € inc.

VAT

Réf: H11383



VRDM-SPLIT

249,00 € inc.

VAT

Réf: H11546

Galerie photos

