



VBAR-50RGBL

Architectural spotlight IP66 12 LEDs RGBL 50 W 12° - 2 zones

Référence: H11381

549,00 € inc. VAT



- Power: 50 W
- LEDs: 12 LEDs 4 W 4 in 1 (Red, Green, Blue, Lime)
- Lens opening: 12°.
- LED zones: 2 zones
- Brightness: 2655 lm - 960 lux at 5 m
- Power consumption: 52 W
- Dimensions: 484 x 117 x 53 mm
- Weight: 3.7 kg
- Connections: DMX/Power via hybrid IN and OUT cables with IP67 plugs
- Parameterization: VRDM-Control external box for RDM parameterization
- RDM console compatibility: Yes, for basic parameters (DMX address, DMX mode, version, etc.).
- How to use :
 - Standalone (Master/Slave and Single)
 - DMX: 2 channels
- Macro: Create your own macros for use in Master/Slave or Single mode.
- Power supply: 110-240 V / 50-60 Hz
- Refresh rate: Selectable from 900 Hz to 3600 Hz
- Cooling : Convection
- Finish: Cast aluminium, epoxy-painted grey-white RAL 9002
- Degree of protection: IP66 (resistant to dust and water spray from all directions)
- Shock resistance: IK07 (protected against a drop of 2 joules, object weighing 500 g dropped from 40 cm)
- Pressure control: Sealed diaphragm depressurization valve
- Accessories: VC-Start power cord, IP plugs, flow switch.

Caractéristiques

Brand	Contest Architectural Lighting
Controllable colours	Lime, RGBL
Power	50 W
Protocole	DMX, RDM
Type de lampe	LED

Références compatibles



VRDM-CONTROL

379,00 € inc.

VAT

Réf: H11383



VRDM-SPLIT

249,00 € inc.

VAT

Réf: H11546

Galerie photos

