



## VCOB-60RGBL

IP66 COB RGBL LED 60 W 60° architectural spotlight

Référence: H11376

**519,00 € inc. VAT**



- Power: 60 W
- LEDs: COB 60 W 4 in 1 (Red, Green, Blue, Lime)
- Lens opening: 60°.
- Brightness: 2893 lm - 80 lux at 5 m
- Power consumption: 60 W
- Dimensions: 180 x 117 x 221 mm
- Weight: 3.7 kg
- Connections: DMX/Power via hybrid IN and OUT cables with IP67 plugs
- Parameterization: VRDM-Control external box for RDM parameterization
- RDM console compatibility: Yes, for basic parameters (DMX address, DMX mode, version, etc.).
- How to use :
  - Standalone: Master/Slave and Single
  - DMX: 2 to 8 channels
- Macro: Create your own macros for use in Master/Slave or Single mode
- Power supply: 110-240 V / 50-60 Hz
- Refresh rate: Selectable from 900 Hz to 3600 Hz
- Cooling : Convection
- Finish: Cast aluminium, epoxy-painted grey-white RAL 9002
- Degree of protection: IP66 (protected against dust and splashing water)
- Shock resistance: IK07 (protected against a drop of 2 joules, object weighing 500 g falling from a height of 40 cm)
- Pressure control: Sealed diaphragm depressurization valve
- Accessories: VC-Start power cord, IP plugs, shutter

## Caractéristiques

|                             |                                |
|-----------------------------|--------------------------------|
| <b>Brand</b>                | Contest Architectural Lighting |
| <b>Controllable colours</b> | Lime, RGBL                     |
| <b>Power</b>                | 60 W                           |
| <b>Protocole</b>            | DMX, RDM                       |
| <b>Type de lampe</b>        | COB                            |

## Références compatibles



**VRDM-CONTROL**

**379,00 € inc.**

**VAT**

Réf: H11383



**VRDM-SPLIT**

**249,00 € inc.**

**VAT**

Réf: H11546

## Galerie photos



