



VPANEL-200RGBL

Référence: H11547

1399,00 € inc. VAT



IP66 24 LED RGBL 200 W 30° architectural spotlight

Optics

24 LEDs of 20 W 4 in 1 RGBL

- ' Double structured lenses for perfect beam diffusion
- ' Symmetrical lenses with 30° aperture

Brightness

- 6352 lm - 1080 lux at 5 m

Connections

- DMX/Power connections via hybrid IN and OUT cables with IP 67 plugs

Features

- Control via external VRDM-Control box for parameter setting via RDM
- Compatible with RDM consoles on certain parameters.
- DMX control protocol on 2 to 20 channels depending on the selected mode
- Power supply: 110-240V/50-60 Hz
- Consumption: 207 W
- Selectable refresh rate from 900 Hz to 3600 Hz.
- Cooling: convection
- Finishes: cast aluminium, epoxy-painted grey-white RAL 9002
- IP 66 protection rating: resists dust and water splashes from all directions
- Shock resistance IK 07: protected against a mechanical shock of 2 joules, i.e. an object weighing 500 g dropped from a height of 40 cm.
- Sealed diaphragm depressurization valve
- Dimensions: 582 x 270 x 178 mm
- Weight: 15 kg

Caractéristiques

Brand	Contest Architectural Lighting
Controllable colours	Lime, RGBL
Power	200 W
Protocole	DMX, RDM
Type de lampe	LED

Accessoires recommandés



VRDM-CONTROL

379,00 € inc. VAT
Réf: H11383



VRDM-SPLIT

249,00 € inc. VAT
Réf: H11546

Galerie photos



 **hitmusic**
Fabrique sensorielle

www.hitmusic.eu/en/