



## VPANEL-200RGBL

IP66 24 LED RGBL 200 W 30° architectural spotlight

Référence: H11547

**1399,00 € inc. VAT**



- Power: 200 W
- LEDs: 24 x 20 W LEDs (4 in 1 RGLB)
- Lens aperture :
  - Double structured lenses for perfect beam diffusion
  - Symmetrical lenses with 30° aperture
- Power consumption: 207 W
- Brightness: 6352 lm - 1080 lux at 5 m
- Dimensions: 585 x 270 x 178 mm
- Weight: 7 kg
- Connections: DMX/Power via hybrid IN and OUT cables with IP67 plugs
- Parameterization: VRDM-Control external box for RDM parameterization
- RDM console compatibility :
  - Yes, on basic parameters (DMX address, DMX mode, version, etc.)
- How to use :
  - Standalone: Master/Slave and Single
  - DMX: 2 to 20 channels
- Macro: Macros can be created for use in Master/Slave or Single mode.
- Power supply: 110-240 V / 50-60 Hz
- Refresh rate: Selectable from 900 Hz to 3600 Hz
- Cooling : Convection
- Finish: Cast aluminium, epoxy-painted grey-white RAL 9002
- Degree of protection: IP66 (resistant to dust and water spray from all directions)
- Shock resistance: IK07 (protected against an impact of 2 joules, equivalent to a 500 g object falling from 40 cm)
- Pressure control: Sealed diaphragm depressurization valve
- Accessories: VC-Start power cord, IP plugs, flow switch

## Caractéristiques

<b>Brand</b>	Contest Architectural Lighting
<b>Controllable colours</b>	Lime, RGLB
<b>Power</b>	200 W
<b>Protocole</b>	DMX, RDM
<b>Type de lampe</b>	LED

## Références compatibles



**VRDM-CONTROL**

**379,00 € inc.**

**VAT**

Réf: H11383



**VRDM-SPLIT**

**249,00 € inc.**

**VAT**

Réf: H11546

## Galerie photos



