



VPAR-120DW

Référence: H11552

759,00 € inc. VAT



IP66 architectural spotlight 12 DW 2700 - 6000 K 120 W 25° LEDs

LED

- 12 x LEDs 15 W Dynamic White 2700-6000K
- Symmetrical lenses with 25° aperture

Brightness

- 4669 lm - 903 lux at 5 m

CRI

- 96

Consumption

- 120 W

Dimensions

- 157 x 240 x 254 mm

Weight

- 5.5 kg

Connections

- DMX/Power connections via hybrid IN and OUT cables with IP 67 plugs

Features

- External VRDM-Control box for RDM parameterization
- Compatible with RDM consoles on certain parameters
- DMX control protocol on 2 to 4 channels depending on the selected mode
- Power supply: 110-240 V/50-60 Hz
- Selectable refresh rate from 900 Hz to 3600 Hz
- Cooling: convection
- Finish: cast aluminium, epoxy-painted grey-white RAL 9002
- IP 66 protection: dust- and splash-proof from all directions
- Shock resistance IK 07: protected against a mechanical shock of 2 joules, i.e. an object weighing 500 g dropped from a height of 40 cm.
- Sealed diaphragm depressurization valve

Caractéristiques

Brand	Contest Architectural Lighting
Controllable colours	Cold white, Natural white, Warm white
Power	120 W
Protocole	DMX, RDM
Type de lampe	LED

Galerie photos

