

VERSATILE SPOTLIGHTS

VPAR-150RGBL

Contest[®] 
ARCHITECTURAL LIGHTING

Part no. H11548 EAN 3662009026275

Warning:

18×20 W 4-in-1 RGBL (Red, Green, Blue, Lime) LED spotlight, 25° lens, 6285 lm. IP66 & IK07, DMX 2-8 channels, RDM via external housing. Passive cooling, RAL 9002 aluminum housing. Standalone or DMX modes. IP67 connections. Supplied with VC-Start cable, IP plugs and barn doors.



PRODUCT PAGE ONLINE

architectural-lighting.eu/specs-vpar-rgb1

Manuals, compatible accessories and updates — scan the code or click the address.

Technical specifications

Power	150 W
LEDs	18 x 20 W 4-in-1 LEDs (Red, Green, Blue, Lime)
Lens opening	25°.
Brightness	6285 lm - 1270 lux at 5 m
Power consumption	153 W
Dimensions	157 x 269 x 291 mm
Weight	7 kg
Connections	DMX/Power via hybrid IN and OUT cables with IP67 plugs
Parameterization	VRDM-Control external box for RDM parameterization
RDM console compatibility	Yes, for basic parameters (DMX address, DMX mode, version, etc.).
	How to use :
Standalone	Master/Slave and Single
DMX	2 to 8 channels
Macro	Macros can be created for use in Master/Slave or Single mode.
Power supply	110-240 V / 50-60 Hz
Refresh rate	Selectable from 900 Hz to 3600 Hz
Cooling	Convection
Finish	Cast aluminium, epoxy-painted grey-white RAL 9002
Degree of protection	IP66 (protected against dust and splashing water)
Shock resistance	IK07
Pressure control	Sealed diaphragm depressurization valve

Accessories

VC-Start power cord, IP plugs, flow switch.

Overview

Warning:

these fixtures are not treated against corrosion in saline environments. Use at the seaside or in heavily salt-laden atmospheres may cause premature deterioration of their components.

Compatible accessories



VRDM-CONTROL

H11383



VRDM-SPLIT

H11546

Photo



Photo

