



VPAR-150RGBL

IP66 18 LED RGBL 150 W 25° architectural spotlight

Référence: H11548

1049,00 € inc. VAT



- Power: 150 W
- LEDs: 18 x 20 W 4-in-1 LEDs (Red, Green, Blue, Lime)
- Lens opening: 25°.
- Brightness: 6285 lm - 1270 lux at 5 m
- Power consumption: 153 W
- Dimensions: 157 x 269 x 291 mm
- Weight: 7 kg
- Connections: DMX/Power via hybrid IN and OUT cables with IP67 plugs
- Parameterization: VRDM-Control external box for RDM parameterization
- RDM console compatibility: Yes, for basic parameters (DMX address, DMX mode, version, etc.).
- How to use :
 - Standalone: Master/Slave and Single
 - DMX: 2 to 8 channels
- Macro: Macros can be created for use in Master/Slave or Single mode.
- Power supply: 110-240 V / 50-60 Hz
- Refresh rate: Selectable from 900 Hz to 3600 Hz
- Cooling : Convection
- Finish: Cast aluminium, epoxy-painted grey-white RAL 9002
- Degree of protection: IP66 (protected against dust and splashing water)
- Shock resistance: IK07
- Pressure control: Sealed diaphragm depressurization valve
- Accessories: VC-Start power cord, IP plugs, flow switch.

Caractéristiques

Brand	Contest Architectural Lighting
Controllable colours	Lime, RGBL
Power	150 W
Protocole	DMX, RDM
Type de lampe	LED

Références compatibles



VRDM-CONTROL

379,00 € inc.

VAT

Réf: H11383



VRDM-SPLIT

249,00 € inc.

VAT

Réf: H11546

Galerie photos



