



VPAR-70DW

Référence: H11553

649,00 € inc. VAT



IP66 architectural spotlight 7 DW 2700 - 6100 K 70 W 25° LEDs

LED

- 7 x LEDs 15 W Dynamic White 2700-6000 K
- Symmetrical lenses with 25° aperture

Brightness

- 2594 lm - 531 lux at 5 m

CRI

- 96

Consumption

- 70 W

Dimensions

- 224 x 117 x 221 mm

Weight

- 3.5 kg

Connections

- DMX/Power connections via hybrid IN and OUT cables with IP 67 plugs

Features

- External VRDM-Control box for RDM parameterization
- Compatible with RDM consoles on certain parameters
- DMX control protocol on 2 to 4 channels depending on the selected mode
- Power supply: 110-240 V/50-60 Hz
- Selectable refresh rate from 900 Hz to 3600 Hz
- Cooling: convection
- Finish: cast aluminium, epoxy-painted grey-white RAL 9002
- IP 66 protection: dust- and splash-proof from all directions
- Shock resistance IK 07: protected against a mechanical shock of 2 joules, i.e. an object weighing 500 g dropped from a height of 40 cm.
- Sealed diaphragm depressurization valve

Caractéristiques

Brand	Contest Architectural Lighting
Controllable colours	Cold white, Natural white, Warm white
Power	70 W
Protocole	DMX, RDM
Type de lampe	LED

Galerie photos

