



VPAR-70RGBL

Référence: H11550

669,00 € inc. VAT



Architectural spotlight IP66 7 LED RGBL 70 W 25°.

LED

- 7x LEDs 20 W 4 in 1 Red Green Blue Lime
- Symmetrical lenses with 25° aperture

Brightness

- 2165 lm - 428 lux at 5 m

Power consumption

- 72 W

Dimensions

- 224 x 117 x 221 mm

Weight

- 3.5 kg

Connections

- DMX/Power connections via hybrid IN and OUT cables with IP67 plugs

Features

- External VRDM-Control box for RDM parameterization
- Compatible with RDM consoles on certain parameters
- DMX control protocol on 2 to 8 channels depending on the selected mode
- Power supply: 110-240 V/50-60 Hz
- Selectable refresh rate from 900 Hz to 3600 Hz
- Cooling: convection
- Finish: cast aluminium, epoxy-painted grey-white RAL 9002
- IP66 protection rating: resists dust and water splashes from all directions
- Shock resistance IK07: protected against a mechanical shock of 2 joules, i.e. an object weighing 500 g dropped from a height of 40 cm.
- Sealed diaphragm depressurization valve

Caractéristiques

Brand	Contest Architectural Lighting
Controllable colours	Lime, RGBL
Power	70 W
Protocole	DMX, RDM
Type de lampe	LED

Accessoires recommandés



VRDM-CONTROL

379,00 € inc. VAT
Réf: H11383



VRDM-SPLIT

249,00 € inc. VAT
Réf: H11546

Galerie photos

